

RANGO DE PRINCIPALES PERFILES

RETENES								
CODIGO	materiales principales				Temperat.		Veloc.	Pres.
	CROQUIS				min	max	max	max
détalle					(°C)	(°C)	(m/s)	(MPa)
R01A	retén	respaldo	resorte					
estándar simple labio c/respaldo		HPU (P2)	POM (R1) METAL	METAL	-20	+115	7,0	0,05
		NBR (G1)	POM (R1) METAL	METAL	-30	+110	7,0	0,05
		FKM (G2)	METAL	METAL	-20	+220	7,0	0,05
		EPDM (G3)	METAL	METAL	-45	+130	7,0	0,05
R01B	retén	resorte						
estándar simple labio c/respaldo		HPU (P2)	METAL	-20	+115	7,0	0,05	
		NBR (G1)	METAL	-30	+110	7,0	0,05	
		FKM (G2)	METAL	-20	+220	7,0	0,05	
		EPDM (G3)	METAL	-45	+130	7,0	0,05	
R02A	retén	respaldo	resorte					
estándar doble labio c/respaldo		HPU (P2)	POM (R1) METAL	METAL	-20	+115	7,0	0,05
		NBR (G1)	POM (R1) METAL	METAL	-30	+110	7,0	0,05
		FKM (G2)	METAL	METAL	-20	+220	7,0	0,05
		EPDM (G3)	METAL	METAL	-45	+130	7,0	0,05
R02B	retén	resorte						
estándar doble labio c/respaldo		HPU (P2)	METAL	-20	+115	7,0	0,05	
		NBR (G1)	METAL	-30	+110	7,0	0,05	
		FKM (G2)	METAL	-20	+220	7,0	0,05	
		EPDM (G3)	METAL	-45	+130	7,0	0,05	
R03A	retén	o´ring						
banda deslizante plana c/o´ring		PTFE c/mol (T2)	NBR (G1)	-30	+110	1,0	30	
		PTFE c/mol (T2)	FKM (G2)	-20	+220	1,0	30	
		PTFE c/mol (T4)	NBR (G1)	-30	+110	1,0	30	
		PTFE c/mol (T4)	FKM (G2)	-20	+220	1,0	30	
R04A								
V-ring S		HPU (P2)		-20	+115	10,0	-	
		NBR (G1)		-30	+110	10,0	-	
		FKM (G2)		-20	+220	10,0	-	
		EPDM (G3)		-45	+130	10,0	-	
R04B								
V-ring A		HPU (P2)		-20	+115	10,0	-	
		NBR (G1)		-30	+110	10,0	-	
		FKM (G2)		-20	+220	10,0	-	
		EPDM (G3)		-45	+130	10,0	-	