











RANGO DE PRINCIPALES PERFILES

SELLOS DE PISTON						
CODIGO	materiales principales		Temperat.		Veloc.	Pres.
			min	max	max	max
			(°C)	(°C)	(m/s)	(MPa)
detalle						
P01A		HPU (P2)	-20	+115	0,5	40
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16
P01B		HPU (P2)	-20	+115	0,5	40
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16
P01C		HPU (P2)	-20	+115	0,5	40
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16
P01D		HPU (P2)	-20	+115	0,5	40
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16
P02A		sello				
		o'ring				
		HPU (P2)	-20	+115	0,5	40
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16
P02B		sello				
		o'ring				
		HPU (P2)	-20	+115	0,5	40
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16
P03A		sello				
		respaldo				
		HPU (P2)	-20	+115	0,5	50
		NBR (G1)	-30	+110	0,5	20
		FKM (G2)	-20	+220	0,5	20
		EPDM (G3)	-45	+130	0,5	20
P03B		sello				
		respaldo				
		HPU (P2)	-20	+115	0,5	50
		NBR (G1)	-30	+110	0,5	20
		FKM (G2)	-20	+220	0,5	20
		EPDM (G3)	-45	+130	0,5	20
P04A		sello				
		respaldo				
		o'ring				
		HPU (P2)	-20	+115	0,5	50
		NBR (G1)	-30	+110	0,5	20
		FKM (G2)	-20	+220	0,5	20
		EPDM (G3)	-45	+130	0,5	20
P04B		sello				
		respaldo				
		o'ring				
		HPU (P2)	-20	+115	0,5	50
		NBR (G1)	-30	+110	0,5	20
		FKM (G2)	-20	+220	0,5	20
		EPDM (G3)	-45	+130	0,5	20
P05A		sello				
		o'ring				
		PTFE c/mol (T2)	-30	+110	10,0	40
		PTFE c/mol (T2)	-20	+220	10,0	40
		PTFE c/brce (T4)	-30	+110	10,0	50
		PTFE c/brce (T4)	-20	+220	10,0	50

SELLOS DE PISTON (cont.)						
CODIGO	materiales principales		Temperat.		Veloc.	Pres.
			min	max	max	max
			(°C)	(°C)	(m/s)	(MPa)
detalle						
P05B		sello				
		o'ring				
		PTFE c/mol (T2)	-30	+110	10,0	40
		PTFE c/mol (T2)	-20	+220	10,0	40
		PTFE c/brce (T4)	-30	+110	10,0	50
		PTFE c/brce (T4)	-20	+220	10,0	50
P05C		sello				
		o'ring				
		PTFE c/mol (T2)	-30	+110	10,0	30
		PTFE c/mol (T2)	-20	+220	10,0	30
		PTFE c/brce (T4)	-30	+110	10,0	35
		PTFE c/brce (T4)	-20	+220	10,0	35
P05D		sello				
		o'ring				
		PTFE c/mol (T2)	-30	+110	10,0	40
		PTFE c/mol (T2)	-20	+220	10,0	40
		PTFE c/brce (T4)	-30	+110	10,0	50
		PTFE c/brce (T4)	-20	+220	10,0	50
P06A		sello				
		Cargador				
		PTFE c/mol (T2)	-30	+110	10,0	40
		PTFE c/mol (T2)	-20	+220	10,0	40
		PTFE c/brce (T4)	-30	+110	10,0	50
		PTFE c/brce (T4)	-20	+220	10,0	50
P07N		intermedias				
		base				
		tapa				
		HPU (P2)	-20	+115	0,5	50
		NBR (G1)	-30	+110	0,5	20
		FKM (G2)	-20	+220	0,5	20
		EPDM (G3)	-45	+130	0,5	20
P08A		sello				
		respaldos				
		HPU (P2)	-20	+115	0,5	50
		NBR (G1)	-30	+110	0,5	20
		FKM (G2)	-20	+220	0,5	20
		EPDM (G3)	-45	+130	0,5	20
P09A		HPU (P2)	-20	+115	0,5	16
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16
P10A		HPU (P2)	-20	+115	0,5	16
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16
P12A		sello				
		cargador				
		respaldos				
		PTFE c/mol (T2)	-30	+110	1,5	30
		PTFE c/mol (T2)	-20	+220	1,5	30
		PTFE c/brce (T4)	-30	+110	1,5	40
		PTFE c/brce (T4)	-20	+220	1,5	40
P12B		sello				
		cargador				
		respaldos				
		PTFE c/mol (T2)	-30	+110	1,5	30
		PTFE c/mol (T2)	-20	+220	1,5	30
		PTFE c/brce (T4)	-30	+110	1,5	40
		PTFE c/brce (T4)	-20	+220	1,5	40
P15A		sello				
		o'ring				
		HPU (P2)	-20	+115	0,5	40
		NBR (G1)	-30	+110	0,5	16
		FKM (G2)	-20	+220	0,5	16
		EPDM (G3)	-45	+130	0,5	16

RANGO DE PRINCIPALES PERFILES

SELLOS DE PISTON (cont.)							
CODIGO	detalle	materiales principales			Temperat.		Pres.
					min	max	max
					(°C)	(°C)	(MPa)
P16A	 Banda deslíz. y quadring c/o'ring						
		sello	o'ring	quad-ring			
		PTFE c/mol (T2)	NBR (G1)	NBR (G1)	-30	+110	2,0 30
		PTFE c/mol (T2)	FKM (G2)	FKM (G2)	-20	+220	2,0 30
		PTFE c/brce (T4)	NBR (G1)	NBR (G1)	-30	+110	2,0 40
P16B	 banda deslíz. y quadring c/2 o'ring						
		sello	o'ring	quad-ring			
		PTFE c/mol (T2)	NBR (G1)	NBR (G1)	-30	+110	3,0 40
		PTFE c/mol (T2)	FKM (G2)	FKM (G2)	-20	+220	3,0 40
		PTFE c/mol (T4)	NBR (G1)	NBR (G1)	-30	+110	3,0 50
P22A	 Compacto una pieza						
		HPU (P2)			-20	+115	0,5 40
		NBR (G1)			-30	+110	0,5 16
		FKM (G2)			-20	+220	0,5 16
		EPDM (G3)			-45	+130	0,5 16
P23A	 U con o'ring y pedestal						
		sello u	pedestal	o'ring			
		HPU (P2)	HPU (P2)	NBR (G1)	-20	+115	0,5 40
		NBR (G1)	NBR (G1)	NBR (G1)	-30	+110	0,5 16
		FKM (G2)	FKM (G2)	FKM (G2)	-20	+220	0,5 16
P77N	 paquete doble sello apilado						
		s. anterior	s. posterior				
		HPU (P2)	HPU (P2)		-20	+115	0,5 50
		NBR (G1)	NBR (G1)		-30	+110	0,5 20
		FKM (G2)	FKM (G2)		-20	+220	0,5 20
		EPDM (G3)	EPDM (G3)		-45	+130	0,5 20